

FEATURES & SPECIFICATIONS

INTENDED USE

Provides general illumination in commercial and residential applications. Ideal for use in closets, hallways, pantries, corridors, utility areas and more.

CONSTRUCTION

Features a white acrylic diffuser with either a pull chain or passive infrared (PIR) sensor for easy on/off operation. The PIR sensor activates when motion is detected. After 30 seconds of no motion, the fixture automatically turns off.

OPTICS

The FMMCL produces 575 lumens (7"), 925 lumens (18"), and 1,225 lumens (24") at 50,000 hours life (see chart below).

ELECTRICAL

Fixture operates at 120 volts, 60 Hz. Standard input wattage noted in chart below.

INSTALLATION

All mounting hardware included. Easily installs in minutes and can be flush mounted to walls or ceilings.

LISTINGS

cUL Certified to US and Canadian standards and listed suitable for damp locations. ENERGY STAR® certified.

WARRANTY

5-year limited warranty. Complete warranty terms located at www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

NOTE: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25°C. Specifications subject to change without notice.

	Lumens	Wattage	LPW
7"	575	10.4	55
18"	925	14	66
24"	1,225	17	72

Catalog Number
Notes
Type

Decorative Indoor

LED Closet Light

Flush Mount



HIGH-PERFORMANCE LED



Specifications

	7"	18"	24"
Height:	4-1/4 (10.8)	3-1/4 (8.2)	3-1/4 (8.2)
Width:	6-5/8 (16.8)	17-6/8 (45)	23-5/8 (60)
Depth:	1-5/8 (4.1)	1-3/8 (3.6)	1-3/8 (3.6)
Weight:	.88 lb (.4 kg)	1 lb (.5 kg)	1.5 lb (.7 kg)

All dimensions are inches (centimeters) unless otherwise indicated.

ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

Example: FMMCL 840 S1




Series ¹	Width	CRI/Color Tempertaure	Controls
FMMCL LED closet light	(blank) 7" 18 18" 24 24"	840 85 CRI, 4000K	S1 Pull chain PIR Passive infrared sensor

Notes

1 Use with non-dimmable switches only.

LED Closet Light

LIGHTING FACTS



PHOTOMETRICS

Full photometric data report available within 2 weeks from request. Consult factory.