

## Disconnects - Metal Case



TDDS-60

- Fused models designed with fuses in pull out handle for easy replacement
- Fused models have indicator lights for blown fuses.
- The line, load, and ground terminals are aligned for ease of wiring
- Reversible door which opens to either the left or right.
- Side open door opens more than 180° for maximum access and has a full dead front.
- Rain tight and sleet resistant.
- The UL Listed number is IRF9, NEMA Type 3R and the US Patent is 6,630,637.

CAT. NO.	DESCRIPTION	UOM	ORDER MULTIPLE
TDDS-30	30A FUSIBLE DISCONNECT SWITCH	EA	1
TDDS-60	60A FUSIBLE DISCONNECT SWITCH	EA	1
TDDS-60U	60A NON-FUSIBLE DISCONNECT SWITCH	EA	1

## Disconnect - Non-Metallic Case



T750-P60NF

- 60 amp non-fusible disconnect is housed in a lightweight, non-metallic case.
- Features a side opening door with more than 180° access, full dead front, and a locking tab
- U.L. and C.U.L. Listed.

CAT. NO.	DESCRIPTION	UOM	ORDER MULTIPLE
T750-P60NF	60A NON FUSIBLE DISCONNECT SWITCH, NON-METALLIC CASE, PLASTIC	EA	1