



YRA26U

by Burndy Catalog ID: YRA26U

Prop 65 Notice

AL compression lug for joining AL and CU cable to transformer and equiptment pads, Prefilled with PENETROX, 3.19 IN L.

Features: Aluminum HYLUG For Joining Aluminum And Copper Cable To Transformer And Equipment Pads, HYLUG Is Pre-Filled With PENETROX Joint Compound And Capped, Installed With Standard Tooling, Five Die Sets Install Fourteen Terminal Size, Overlap Crimps, Tools, Die Set Catalog Number, And (number Of Crimps): MD6, MD7 Tool, W249, WK840 Die, Y35, Y750 Tool, U249, UK-840 Die, Y45 Tool, U249, UK-840 Die With PT-6515 Adapter, Y46 Tool, U249, UK-840 Die With PUADP-1 Adapter, Die Index: 249 Or K840, Tongue Angle: Straight, Conductor Type: ACSR, Copper, Aluminum Concentric And Compact

Product Details

General

Application	For Joining Aluminum And Copper Cable To Transformer And Equipment Pads
Die Index	249;K-840
Material	Aluminum
Physical Attribute - Pad Configuration	1 Hole
Physical Attribute - Tongue Type	Standard
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	HYLUG
Trade Name	HYLUG™
Туре	YRA
UPC	781810810163
UPC 12 Digit	7818108101633

Dimensions

Dimension - B Length fraction	3-1/4 in
Dimension - B Length inch	1.43 in
Dimension - D inch	1.28 in
Dimension - L Length Overall mm	81 mm
Dimension - Length Overall inch	3.19 in
Dimension - N inch	0.62 in
Dimension - Outside Diameter inch	0.91 in
Dimension - Pad Width inch	0.91 in
Dimension - Strip Length inch	11/2 in
Physical Attribute - Tongue Angle	Straight
Thickness - Pad	0.25 in

Conductor Related

Conductor - ACSR Str Size	2/0 AWG
Conductor - AL Str Size	2/0 AWG
Conductor - Copper Str Size	2/0 AWG

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	СМ
UL Listed	No

Logistics

Minimum Pack Quantity	50	
Tillinant dex eduncty	30	

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days Phone: 1-800-346-4175 1-603-647-5299 (International)