

MINITERMS

Spade Terminals

S Series

SPECIFICATIONS

- Vinyl: Electro tin plated copper, vinyl (PVC) 300V, 75 °C.
- Un-Insulated: Electro tin plated copper, 600V, 105 °C.

FEATURES

- Vinyl and Un-Insulated Spade Terminal have open tongue end for rapid insertion on the mounting screw. Typically used on free-standing studs.



FIG. NO.	INSULATION TYPE	WIRE RANGE	STUD SIZE	RATINGS	LENGTH (L) (IN.)	WIDTH (W) (IN.)	SEAM TYPE	"S" PACKS		PRO PACKS		STD PACKS		BULK PACKS	
								CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY
1	Vinyl	22-18	1/4	cULus	1.070	0.472	Butted	—	—	—	—	S22-14V	100	S22-14V-BULK	1000
1	Vinyl	22-18	#10	cULus	0.826	0.374	Butted	S22-10V-S	25	S22-10V-P	100	S22-10V	100	S22-10V-BULK	1000
1	Vinyl	22-18	#4	cULus	0.817	0.251	Butted	—	—	—	—	S22-4V	100	S22-4V-BULK	1000
1	Vinyl	22-18	#6	cULus	0.826	0.228	Butted	S22-6V-S	25	S22-6V-P	100	S22-6V	100	S22-6V-BULK	1000
1	Vinyl	22-18	#8	cULus	0.826	0.283	Butted	S22-8V-S	25	S22-8V-P	100	S22-8V	100	S22-8V-BULK	1000
1	Vinyl	16-14	1/4	cULus	0.812	0.543	Butted	—	—	—	—	S16-14V	100	S16-14V-BULK	1000
1	Vinyl	16-14	#10	cULus	0.966	0.362	Butted	S16-10V-S	20	S16-10V-P	85	S16-10V	100	S16-10V-BULK	1000
1	Vinyl	16-14	#6	cULus	0.966	0.388	Butted	S16-6V-S	20	S16-6V-P	85	S16-6V	100	S16-6V-BULK	1000
1	Vinyl	16-14	#8	cULus	1.103	0.388	Butted	S16-8V-S	20	S16-8V-P	85	S16-8V	100	S16-8V-BULK	1000
1	Vinyl	12-10	1/4	cULus	1.103	0.375	Butted	S12-14V-S	12	S12-14V-P	40	S12-14V	50	S12-14V-BULK	500
1	Vinyl	12-10	#10	cULus	1.103	0.375	Butted	S12-10V-S	15	S12-10V-P	50	S12-10V	50	S12-10V-BULK	500
1	Vinyl	12-10	#6	cULus	1.103	0.375	Butted	S12-6V-S	15	S12-6V-P	50	S12-6V	50	S12-6V-BULK	500
1	Vinyl	12-10	#8	cULus	0.690	0.316	Butted	S12-8V-S	15	S12-8V-P	50	S12-8V	50	S12-8V-BULK	500
2	Un-insulated	22-18	#10	UL	0.623	0.251	Brazed	—	—	—	—	S22-10	100	S22-10-BULK	1000
2	Un-insulated	22-18	#4	UL	0.629	0.228	Brazed	—	—	—	—	S22-4	100	S22-4-BULK	1000
2	Un-insulated	22-18	#6	cULus	0.778	0.316	Brazed	—	—	—	—	S22-6	100	S22-6-BULK	1000
2	Un-insulated	22-18	#8	UL	0.770	0.388	Brazed	—	—	—	—	S22-8	100	S22-8-BULK	1000
2	Un-insulated	16-14	#10	cULus	0.638	0.245	Brazed	—	—	S16-10-P	100	S16-10	100	S16-10-BULK	1000
2	Un-insulated	16-14	#6	cULus	0.635	0.295	Brazed	—	—	—	—	S16-6	100	S16-6-BULK	1000
2	Un-insulated	16-14	#8	UL	1.000	0.492	Brazed	—	—	S16-8-P	100	S16-8	100	S16-8-BULK	1000
2	Un-insulated	12-10	1/4	—	0.812	0.375	Brazed	—	—	—	—	S12-14	50	S12-14-BULK	1000
2	Un-insulated	12-10	#10	cULus	0.812	0.375	Brazed	—	—	—	—	S12-10	50	S12-10-BULK	1000
2	Un-insulated	12-10	#6	UL	0.812	0.375	Brazed	—	—	—	—	S12-6	50	S12-6-BULK	1000
2	Un-insulated	12-10	#8	cULus	0.953	0.471	Brazed	—	—	—	—	S12-8	50	S12-8-BULK	1000
2	Un-insulated	8	1/4	—	0.956	0.471	Brazed	—	—	—	—	S8-14	50	S8-14-BULK	100
2	Un-insulated	8	#10	—	1.033	0.322	Brazed	—	—	—	—	S8-10	50	S8-10-BULK	100

MINITERMS

Vinyl Insulated Miniterm Kit

MTK, MTK-2

SPECIFICATIONS

- cULus Listed for Quick Connect Terminals.
- cULus Listed Wire Connector.
- Vinyl Insulated: 300V, 75 °C.
- Nylon Insulated: 600V, 105 °C.

FEATURES

- These kits have been carefully designed to include the most popular NSI miniterm terminals.
- Cases are reusable and made of extremely durable polypropylene.
- Kits provide the ultimate in organization and convenience.
- Clearly labeled on the inside lid for easy recognition.
- Convenient size for easy carrying and easy storing.
- Product number ending in "V" is vinyl insulated.
- Crimping tool included with MTK-2



CAT. NO.	FIG. NO.	KIT CONTENTS						STD. CTN. QTY.
		PART NO.	QTY.	PART NO.	QTY.	PART NO.	QTY.	
MTK	1	R22-6V	40	F22-250-3V	40	S22-6V	40	12
		R22-10V	40	F16-250-3V	35	S22-10V	35	
		R16-6V	30	F12-250-3V	20	S16-6V	20	
		R16-10V	30	B22-V	35	S16-10V	35	
		R12-8V	20	B16-V	25	S12-8V	25	
		R12-14V	20	B12-V	15	S12-14V	15	
MTK-2	2	R22-6V	10	S22-8V	10	B22-V	10	12
		R22-8V	10	S22-10V	10	B16-V	10	
		R22-10V	10	S16-8V	10	B12-V	10	
		R16-6V	10	S16-10V	10	F22-250-3V	10	
		R16-8V	10	S12-10V	5	F16-250-3V	10	
		R16-10V	10	M22-250-3V	10	Crimping tool included	1	
		R12-10V	5	M16-250-3V	10			

MINITERMS

Vinyl Insulated Miniterm Kit

MTKL-100



SPECIFICATIONS

- cULus Listed for Quick Connect Terminals.
- cULus Listed Wire Connector.
- Vinyl insulated 300V, 75 °C.

FEATURES

- These kits have been carefully designed to include the most popular NSi miniterm terminals.
- Cases are reusable and made of extremely durable polypropylene.
- Kits provide the ultimate in organization and convenience.
- Clearly labeled on the inside lid for easy identification.
- Convenient size for easy carrying and easy storing.
- Product number ending in "V" is vinyl insulated.
- Product number ending in "N" is nylon insulated.
- Crimping tool included.
- Product number starting with "R" is Ring type.
- Product number starting with "S" is Spade type.
- Product number starting with "M" is Male disconnect type.
- Product number starting with "F" is Female disconnect type.
- Product number starting with "B" is Butt splice type.



CAT. NO.	KIT CONTENTS						STD. CTN. QTY.
	PART NO.	QTY.	PART NO.	QTY.	PART NO.	QTY.	
MTKL-100	TL-5-1	1	C12-N	2	M12-250-3V	2	5
	R12-10V	5	C16-N	4	M16-250-3V	2	
	R16-10V	10	C2-N	5	M22-250-3V	2	
	R22-10V	10	B12-V	6	F12-250-3V	2	
	S12-10V	5	B16-V	10	F16-250-3V	2	
	S16-10V	10	B22-V	10	F22-250-3V	2	
	S22-10V	10					